

SCISSOR PLATFORM TECHNICAL SPECIFICATIONS

MODEL	TKR-MP2000
LIFTING CAPACITY	: 2000
MAX. LİFTİNG	: 1600 mm
MIN. LOWERING	: 400
STROKE	: 1200 mm
TABLE DIMENSIONS	: 2000mm x 2500mm
PICK DIMENSIONS	: 2050 x 2550 x 400mm
SCISSOR GROUP	: 1
PSC OF CYCLINDER	: 2
OPERATING VOLTAGE	: 380V AC
HYDRAULIC POWER UNIT	: 2.2 Kw Motor
STANDART EQUIPMENTS	Popet valve, Hose Blasting Valve, Safety valve, Manometer etc.
LIFTING TIME	:0,15 m/sn
COLOR	: DARK GREY/BLACK/BLUE
CONTROL STYLE	: BUTTON

- **1.** Upper platform,tear drop pattern sheet metal 6/7 mm thickness
- 2. Lip tear drop pattern sheet metal 8/9 mm thickness
- 3. Scissors produced from 100X150X6 mm box profile
- **4.** Handrails are removable and produced from \emptyset 33/3mm pipes
- 5. Hydraulic unit Trademark is **GAMAK**
- **6.** There will be 2 pcs.cylinder to be mounted.
- 7. Inner diameter of cylinders Ø 85mm, outer diameter Ø 105mm
- 8. Shaft 60mm.
- 9. Yellow/Black Warning Bands